

This document shows price extras only. The invoiced price comprises these extras plus basis price, carriage, VAT and any other tax relating to the sale and delivery of the goods.

Basis price

Basis price constitutes the following attributes:

- Minimum of 5 tonnes (per size and length)
- Basis specification (S355JR)
- Standard length
- Net monthly payment terms
- Single delivery point – full unit load
- Order to be placed 8 weeks prior to rolling (ex mill material)
- Material to be taken 2 weeks after date made available (ex mill material)
- Standard service offering

All requirements outside of the basis price will be subject to price extras, as listed. Basis prices are provided by British Steel.

Weight

Material is charged on the calculated weight based on the weight per metre (1 decimal point) as specified in BS4-1, EN10056-2, multiplied by the ordered length. The standard weights are derived from the cross sectional area on the basis of 0.785kg per cm² per metre length. The maximum weight of an individual bar is 15 tonnes. Note: the third element of the section designation is that detailed within the appropriate standard and should not be used to calculate or verify invoiced weights.

Rolling tolerances

All sections are rolled to the tolerances in EN10034, EN10279, EN10056-2, BS4-1. Material will be tested in accordance with the relevant standard.

Test certificates

One copy of the test certificate will be routinely supplied to the customer by British Steel.

Prices

All prices in this list are in GBP/tonne and do not include value-added tax or any other tax relating to the sale and delivery of the goods. All transactions are subject to British Steel's Standard Conditions of Sale. Specifications are subject to acceptance and not all combinations of extras are necessarily available. For specific information about products and their availability, please contact British Steel.

Quality assurance

British Steel has been approved by Lloyd's Register Quality Assurance to EN ISO 9001, including the production and supply of sectional products and extra finishing operations. Additionally, Lloyd's Register has approved British Steel's Section Mills Quality Management Systems and Factory Production Controls in accordance with the Construction Products Directive. As appropriate, British Steel sections will be supplied with a test certificate showing the CE mark.

Terms and conditions of sale

All prices are published or quoted on the basis of British Steel's Standard Conditions of Sale. The latest version of these conditions is available at:

www.britishsteel.co.uk/terms-conditions/

Illustration of price calculation

In most simple terms, the price of sections is determined by adding the following elements of the pricing extras:

- Basis price (customer specific)
- Product extras
- Carriage (customer specific)

Example:

| | |
|-----------------------------|---|
| Section requirements | 20 bars UB 254 x 146 x 43 (11.872 tonnes) |
| Steel specification | EN 10025-2 S355J0 |
| Length | 13,700mm |
| Time order placement | 8 weeks prior to rolling |

Price calculation (per tonne) / £

| | |
|-------------------------------------|-------|
| Basis price | Basis |
| Size extra UB 254 x 146 x 43 | 10 |
| Quality extra | 10 |
| Length extra | 18 |
| Time-based extra | - |
| Quantity extra | 0 |

Note: Price ex basing point, excluding delivery extras - basis plus £38 per tonne and VAT.

Product extras

1. Products

Products have been classified according to weight per linear metre. The table below describes the section size applicable to the weight category and the extra £/tonne applicable per size.

1.1 Universal beams (UB)

| Size | kg/m | Weight group (kg/m) | £/tonne |
|------------------|-------|---------------------|---------|
| 127 x 76 x 13 | 13.0 | 0-20 | 20 |
| 152 x 89 x 16 | 16.0 | 0-20 | 20 |
| 178 x 102 x 19 | 19.0 | 0-20 | 20 |
| 203 x 102 x 23 | 23.1 | 20-70 | 10 |
| 203 x 133 x 30 | 30.0 | 20-70 | 10 |
| x 25 | 25.1 | 20-70 | 10 |
| 254 x 146 x 43 | 43.0 | 20-70 | 10 |
| x 37 | 37.0 | 20-70 | 10 |
| x 31 | 31.1 | 20-70 | 10 |
| 254 x 102 x 28* | 28.3 | 20-70 | 20 |
| x 25 | 25.2 | 20-70 | 10 |
| x 22 | 22.0 | 20-70 | 10 |
| 305 x 102 x 33* | 32.8 | 20-70 | 10 |
| x 28* | 28.2 | 20-70 | 10 |
| x 25 | 24.8 | 20-70 | 10 |
| 305 x 127 x 48* | 48.1 | 20-70 | 10 |
| x 42* | 41.9 | 20-70 | 10 |
| x 37 | 37.0 | 20-70 | 10 |
| 305 x 165 x 54 | 54.0 | 20-70 | 10 |
| x 46 | 46.1 | 20-70 | 10 |
| x 40 | 40.3 | 20-70 | 10 |
| 356 x 127 x 39* | 39.1 | 20-70 | POA |
| x 33* | 33.1 | 20-70 | POA |
| 356 x 171 x 67 | 67.1 | 20-70 | 10 |
| x 57 | 57.0 | 20-70 | 10 |
| x 51 | 51.0 | 20-70 | 10 |
| x 45 | 45.0 | 20-70 | 10 |
| 406 x 140 x 53* | 53.3 | 20-70 | 50 |
| x 46 | 46.0 | 20-70 | 10 |
| x 39 | 39.0 | 20-70 | 10 |
| 406 x 178 x 85* | 85.3 | 70-120 | 50 |
| x 74 | 74.2 | 70-120 | 10 |
| x 67 | 67.1 | 20-70 | 10 |
| x 60 | 60.1 | 20-70 | 10 |
| x 54 | 54.1 | 20-70 | 10 |
| 457 x 152 x 82* | 82.1 | 70-120 | 50 |
| x 74* | 74.2 | 70-120 | 50 |
| x 67 | 67.2 | 20-70 | 50 |
| x 60 | 59.8 | 20-70 | 10 |
| x 52 | 52.3 | 20-70 | 10 |
| 457 x 191 x 161* | 161.4 | 150-200 | 200 |
| x 133* | 133.3 | 120-150 | 180 |
| x 106* | 105.8 | 70-120 | 50 |
| x 98 | 98.3 | 70-120 | 10 |
| x 89 | 89.3 | 70-120 | 10 |
| x 82 | 82.0 | 70-120 | 10 |
| x 74 | 74.3 | 70-120 | 10 |
| x 67 | 67.1 | 20-70 | 10 |

*Subject to availability

| Size | kg/m | Weight group (kg/m) | £/tonne |
|-------------------|-------|---------------------|---------|
| 533 x 165 x 85* | 84.8 | 70-120 | POA |
| x 74* | 74.7 | 70-120 | POA |
| x 66* | 65.7 | 20-70 | POA |
| 533 x 210 x 138* | 138.3 | 120-150 | 180 |
| x 122 | 122.0 | 120-150 | 10 |
| x 109 | 109.0 | 70-120 | 10 |
| x 101 | 101.0 | 70-120 | 10 |
| x 92 | 92.1 | 70-120 | 10 |
| x 82 | 82.2 | 70-120 | 10 |
| 533 x 312 x 272* | 273.3 | 200-300 | POA |
| x 219* | 218.8 | 200-300 | POA |
| x 182* | 181.5 | 150-200 | POA |
| x 150* | 150.6 | 150-200 | POA |
| 610 x 178 x 100* | 100.3 | 70-120 | POA |
| x 92* | 92.2 | 70-120 | POA |
| x 82* | 81.8 | 70-120 | POA |
| 610 x 229 x 140 | 139.9 | 120-150 | 10 |
| x 125 | 125.1 | 120-150 | 10 |
| x 113 | 113.0 | 70-120 | 10 |
| x 101 | 101.2 | 70-120 | 10 |
| 610 x 305 x 238 | 238.1 | 200-300 | 170 |
| x 179 | 179.0 | 150-200 | 160 |
| x 149 | 149.1 | 120-150 | 140 |
| 686 x 254 x 170* | 170.2 | 150-200 | 160 |
| x 152* | 152.5 | 150-200 | 160 |
| x 140 | 140.1 | 120-150 | 140 |
| x 125 | 125.2 | 120-150 | 140 |
| 762 x 267 x 197* | 196.8 | 150-200 | 160 |
| x 173 | 173.0 | 150-200 | 160 |
| x 147 | 146.9 | 120-150 | 140 |
| x 134 | 133.9 | 120-150 | 140 |
| 838 x 292 x 226 | 226.5 | 200-300 | 170 |
| x 194 | 193.8 | 150-200 | 160 |
| x 176 | 175.9 | 150-200 | 160 |
| 914 x 305 x 289 | 289.1 | 200-300 | 170 |
| x 253 | 253.4 | 200-300 | 170 |
| x 224 | 224.2 | 200-300 | 170 |
| x 201 | 200.9 | 200-300 | 170 |
| 914 x 419 x 388 | 388.0 | 300-600 | 200 |
| x 343 | 343.3 | 300-600 | 200 |
| 1016 x 305 x 487* | 487.0 | 300-600 | POA |
| x 438* | 438.0 | 300-600 | POA |
| x 393* | 393.0 | 300-600 | POA |
| x 349* | 349.0 | 300-600 | POA |
| x 314* | 314.0 | 300-600 | POA |
| x 272* | 272.0 | 200-300 | POA |
| x 249* | 249.0 | 200-300 | POA |
| x 222* | 222.0 | 200-300 | POA |



1.2 Universal columns (UC)

| Size | kg/m | Weight group (kg/m) | £/tonne |
|------------------|-------|---------------------|---------|
| 152 x 152 x 51* | 51.2 | 20-70 | 50 |
| x 44* | 44.0 | 20-70 | 50 |
| x 37 | 37.0 | 20-70 | 10 |
| x 30 | 30.0 | 20-70 | 10 |
| x 23 | 23.0 | 20-70 | 10 |
| 203 x 203 x 127* | 127.5 | 120-150 | 180 |
| x 113* | 113.5 | 70-120 | 50 |
| x 100* | 99.6 | 70-120 | 50 |
| x 86 | 86.1 | 70-120 | 10 |
| x 71 | 71.0 | 70-120 | 10 |
| x 60 | 60.0 | 20-70 | 10 |
| x 52 | 52.0 | 20-70 | 10 |
| x 46 | 46.1 | 20-70 | 10 |
| 254 x 254 x 167 | 167.1 | 150-200 | 10 |
| x 132 | 132.0 | 120-150 | 10 |
| x 107 | 107.1 | 70-120 | 10 |
| x 89 | 88.9 | 70-120 | 10 |
| x 73 | 73.1 | 70-120 | 10 |
| 305 x 305 x 283 | 282.9 | 200-300 | 20 |
| x 240 | 240.0 | 200-300 | 20 |
| x 198 | 198.1 | 150-200 | 10 |
| x 158 | 158.1 | 150-200 | 10 |
| x 137 | 136.9 | 120-150 | 10 |
| x 118 | 117.9 | 70-120 | 10 |
| x 97 | 96.9 | 70-120 | 10 |
| 305 x 305 x 283 | 282.9 | 200-300 | 20 |
| x 240 | 240.0 | 200-300 | 20 |
| x 198 | 198.1 | 150-200 | 10 |
| x 158 | 158.1 | 150-200 | 10 |
| x 137 | 136.9 | 120-150 | 10 |
| x 118 | 117.9 | 70-120 | 10 |
| x 97 | 96.9 | 70-120 | 10 |
| 356 x 368 x 202 | 201.9 | 200-300 | 170 |
| x 177 | 177.0 | 150-200 | 170 |
| x 153 | 152.9 | 150-200 | 160 |
| x 129 | 129.0 | 120-150 | 140 |
| 356 x 406 x 634 | 633.9 | 600+ | 300 |
| x 551 | 551.0 | 300-600 | 200 |
| x 467 | 467.0 | 300-600 | 200 |
| x 393 | 393.0 | 300-600 | 200 |
| x 340 | 339.9 | 300-600 | 200 |
| x 287 | 287.1 | 200-300 | 170 |
| x 235 | 235.1 | 200-300 | 170 |

*Subject to availability

1.3 Parallel flange channels (PFC)

| Size | kg/m | £/tonne |
|----------------|------|---------|
| 125 x 65 x 15 | 14.8 | 20 |
| 150 x 75 x 18 | 17.9 | 20 |
| 180 x 75 x 20 | 20.3 | 40 |
| 200 x 75 x 23 | 23.4 | 40 |
| 150 x 90 x 24 | 23.9 | 115 |
| 180 x 90 x 26 | 26.1 | 115 |
| 200 x 90 x 30 | 29.7 | 115 |
| 230 x 75 x 26 | 25.7 | 70 |
| 230 x 90 x 32 | 32.2 | 125 |
| 260 x 75 x 28 | 27.6 | 70 |
| 260 x 90 x 35 | 34.8 | 115 |
| 300 x 90 x 41 | 41.4 | 125 |
| 300 x 100 x 46 | 45.5 | 115 |
| 380 x 100 x 54 | 54.0 | 275 |
| 430 x 100 x 64 | 64.4 | 295 |

1.4 Asymmetric beams (ASB)

| Size | kg/m | S355J0 £/tonne |
|-------------|-------|----------------|
| 280 ASB 74 | 73.6 | POA |
| 280 ASB 100 | 100.3 | POA |
| 280 ASB 105 | 104.7 | POA |
| 280 ASB 124 | 123.9 | POA |
| 280 ASB 136 | 136.4 | POA |
| 300 ASB 153 | 152.8 | POA |
| 300 ASB 155 | 155.4 | POA |
| 300 ASB 185 | 184.6 | POA |
| 300 ASB 196 | 195.5 | POA |
| 300 ASB 237 | 237.1 | POA |
| 300 ASB 249 | 249.2 | POA |

Note: Please be advised that minimum tonnages are required for this particular product. Please contact British Steel for more information.

1.5 Universal bearing piles (UBP)

| Size | kg/m | Weight group (kg/m) | £/tonne |
|-----------------|-------|---------------------|---------|
| 203 x 203 x 54 | 53.9 | 20-70 | 40 |
| x 45 | 44.9 | 20-70 | 40 |
| 254 x 254 x 85 | 85.1 | 70-120 | 40 |
| x 71 | 71.0 | 70-120 | 40 |
| x 63 | 63.0 | 20-70 | 40 |
| 305 x 305 x 223 | 222.9 | 200-300 | 180 |
| x 186 | 186.0 | 150-200 | 180 |
| x 149 | 149.1 | 120-150 | 160 |
| x 126 | 126.1 | 120-150 | 160 |
| x 110 | 110.0 | 70-120 | 40 |
| x 95 | 94.9 | 70-120 | 40 |
| x 88 | 88.0 | 70-120 | 40 |
| x 79 | 78.9 | 70-120 | 40 |
| 356 x 368 x 174 | 173.9 | 150-200 | 180 |
| x 152 | 152.0 | 150-200 | 180 |
| x 133 | 133.0 | 120-150 | 180 |
| x 109 | 108.9 | 70-120 | 40 |

Note: A minimum batch size may apply. Individual requirements for UBP should be discussed with British Steel prior to order placement.

1.6 Equal angles (EA) and unequal angles (UA)

| Size (mm) | kg/m | Thickness (mm) | £/tonne |
|--------------|-------|----------------|---------|
| EA 120 x 120 | 18.2 | 10 | 10 |
| | 21.6 | 12 | 10 |
| | 26.6 | 15 | 10 |
| EA 150 x 150 | 23.0 | 10 | 65 |
| | 27.3 | 12 | 65 |
| | 33.8 | 15 | 65 |
| | 36.0 | 16 | 65 |
| | 40.1 | 18 | 65 |
| EA 200 x 200 | 48.5 | 16 | 65 |
| | 59.9 | 20 | 65 |
| | 71.1 | 24 | 65 |
| | 82.0 | 28 | 65 |
| EA 250 x 250 | 89.9 | 24 | POA |
| | 93.5 | 25 | POA |
| | 97.1 | 26 | POA |
| | 104.0 | 28 | POA |
| | 117.8 | 32 | POA |
| | 128.0 | 35 | POA |
| UA 200 x 100 | 23.0 | 10 | 65 |
| | 27.3 | 12 | 65 |
| | 33.7 | 15 | 65 |
| UA 200 x 150 | 32.0 | 12 | 115 |
| | 39.6 | 15 | 115 |
| | 47.1 | 18 | 115 |



2. Quality

2.1 Basis specification and quality extras

2.1.1 EN10025-2

| EN10025-2 | £/tonne |
|-----------|---------|
| S275JR* | 30 |
| S275J0* | 40 |
| S275J2* | 80 |
| S355JR | Basis |
| S355J0 | 10 |
| S355J2 | 40 |
| S355K2 | 80 |

*Available on referral
Verification of the specified impact value will not be carried out on JR grades (see impact testing page 5).

Notes:

1. The basis price includes all mandatory quality extras associated with the specification
2. The quality extra includes marking to the standard
3. Where customers require additional marking - price on application
4. Where the customer specifies options within the standard, these will be subject to the manufacturer's acceptance, and price extras will be applied as appropriate
5. British Steel offers ultrasonic testing of all sections, as described on page 5
6. Any third party inspectorates and/or ultrasonic testing and/or through thickness testing is price on application

2.1.2 EN10025-4

| EN10025-4 | £/tonne |
|------------------------|---------|
| S355M | POA |
| S355ML (up to 634kg/m) | POA |
| S420M (up to 634kg/m) | POA |
| S420ML (up to 634kg/m) | POA |
| S460M (up to 634kg/m) | POA |
| S460ML (up to 634kg/m) | POA |

Note: Previous specifications (e.g. BS4360) may be supplied, subject to referral.

2.2 Other qualities

2.2.1 Offshore

| EN10025 | Charpy v-notch temp | £/tonne |
|-----------|---------------------|---------|
| S355G1 | -20°C | POA |
| S355G4 | -20°C | POA |
| S355G4+M | -20°C | POA |
| S355G11 | -40°C | POA |
| S355G11+M | -40°C | POA |
| S355G12 | -40°C | POA |
| S355G12+M | -40°C | POA |

2.2.2 Shipbuilding

| Shipbuilding | £/tonne |
|----------------------------------|----------------|
| Lloyd's | By arrangement |
| ABS | By arrangement |
| Other shipbuilding accreditation | By arrangement |

3. Quantity

| Weight (applicable per order line item) | £/tonne |
|---|---------|
| 5 tonnes and over | Basis |
| Under 5 tonnes to 2 tonnes | 25 |
| Under 2 tonnes to 1 tonne | 50 |
| Under 1 tonne to 500kg | 60 |
| Under 500kg to 100kg | POA |

Note: Minimum order charge of £500 will apply.

4. Length

Certain production conditions, which may limit the availability of products over 24,000mm, and individual orders, should be discussed with British Steel.

4.1 Universal beams, columns and bearing piles

| Lengths | £/tonne |
|--|------------------------|
| Standard length: 9,500mm, 11,000mm, 12,200mm, 14,000mm, 15,500mm, 16,500mm, 18,300mm | Basis |
| 6,000mm - 18,300mm in 100mm increments | 18 |
| >18,300mm - 22,000mm in 100mm increments | 50 |
| >22,000mm - 24,000mm in 100mm increments | 100 |
| >24,000mm | Available upon request |

4.2 Parallel flange channels

| Lengths | £/tonne |
|---|---------|
| Standard length: 6,100mm, 9,500mm, 11,000mm, 12,200mm, 14,000mm, 15,500mm | Basis |
| 6,000mm - 18,300mm in 100mm increments | 18 |

4.3 Angles

| Lengths | £/tonne |
|--|---------|
| Standard length: 12,200mm | Basis |
| 6,000mm - 18,300mm in 100mm increments | 30 |

4.4 Asymmetric beams

| Lengths | £/tonne |
|-------------|---------|
| ASB lengths | POA |



5. Further processing

Further processing charges for cutting and mitre cuts are in addition to the length extras specified in tables 4.1, 4.2, 4.3 and 4.4.

5.1 Cutting

| Weights kg/m | Single cut £/cut | Additional cuts £/cut |
|--------------|------------------|-----------------------|
| 0-20kg/m | 4.15 | 1.85 |
| 20-70kg/m | 5.85 | 3.55 |
| 70-120kg/m | 7.35 | 5.05 |
| 120-150kg/m | 10.50 | 7.80 |
| 150-200kg/m | 13.05 | 9.75 |
| 200-300kg/m | 18.00 | 14.70 |
| 300-600kg/m | 33.00 | 28.70 |
| 600+ kg/m | 41.05 | 36.75 |

Notes: Additional cut charges apply only if there is no additional handling and / or machine setup. Standard tolerance 0/-2mm squaring off is charged as an additional cut. Minimum order charge of £45 will apply for processing including cutting, mitre cuts and shotblasting.

5.2 Mitre cuts

| Weights kg/m | Single cut £/cut | Additional cuts £/cut |
|--------------|------------------|-----------------------|
| 0-20kg/m | 5.85 | 6.75 |
| 20-70kg/m | 8.30 | 9.50 |
| 70-120kg/m | 10.40 | 12.00 |
| 120-150kg/m | 14.95 | 17.25 |
| 150-200kg/m | 18.50 | 21.30 |
| 200-300kg/m | 25.50 | 29.40 |
| 300-600kg/m | 46.50 | 53.65 |
| 600+ kg/m | 58.00 | 66.95 |

Notes: Standard tolerance 0/-2mm squaring off is charged as an additional cut. Minimum order charge of £45 will apply for processing including cutting, mitre cuts and shotblasting.

5.3 Shotblasting and painting

| Weights kg/m £/tonne | Shotblasting only | Shotblasting and painting blue | Shotblasting and painting red |
|-------------------------|----------------------|-----------------------------------|----------------------------------|
| 0-20kg/m | 45 | 5.85 | 6.75 |
| 20-70kg/m | 45 | 8.30 | 9.50 |
| 70-120kg/m | 40 | 10.40 | 12.00 |
| 120-150kg/m | 40 | 14.95 | 17.25 |
| 150-200kg/m | 35 | 18.50 | 21.30 |
| 200-300kg/m | 35 | 25.50 | 29.40 |
| 300-600kg/m | 35 | 46.50 | 53.65 |
| 600+ kg/m | 35 | 58.00 | 66.95 |

Notes: Shotblasted and primed to BS EN ISO 8501-1:2007 standard. Shotblast clean to SA 2.5. Paint spec Dr Dermuth water-based weldable primer, 15-25 microns applied.

6. Finishing/markings

For specified applications, tighter tolerances of universal beams (UB), columns (UC) and bearing piles (UBP) can be provided, such that squareness is controlled to half tolerances to a minimum of 3mm and straightness is offered at half tolerances.

6.1 Straightness/squareness

| | £/tonne |
|--------------|---------|
| Straightness | POA |
| Straightness | POA |

Note: This is subject to acceptance by the manufacturing mill and customers are advised to specify this requirement at the time of enquiry and on any subsequently signed offer.

7. Testing and inspection

Inspection authorities' and associated administration charges, including Lloyd's Register and other shipping survey societies will be applied.

7.1 Inspection authorities' fees third party inspection

| | £/tonne |
|---|---------|
| When surface inspection and/or inspection of section dimensional/shape tolerance and section identification marks is to be undertaken in the presence of the purchaser or his representative, this should not interfere with production and/or despatch. A charge will be applied in accordance with the scope of investigation required. | POA |

7.2 Surface inspection

British Steel sections comply with the normal surface condition requirements specified in the appropriate product standard and manufactured in accordance with the appropriate quality control procedures.

| | £/tonne |
|---|---------|
| Special requirements may be accommodated by agreement | POA |

7.3 Ultrasonic testing

| | £/tonne |
|---|---------|
| Testing to EN 10306 and EU 186-187 can be offered* | POA |
| Ultrasonic testing of all sections is provided by British Steel | POA |
| Witnessing** | POA |

Notes:

- Any special requirements regarding limits on internal defects should be agreed at the time of the original order
- Tests not specified and agreed at the time of ordering will not be considered part of the contract
- *Edge testing, as defined in BS 5996, is not available
- **Ultrasonic testing undertaken in the presence of the purchaser or outside inspection authority

7.4 Impact testing

| | £/tonne |
|---|---------|
| Where customers exercise option 3 of EN 10025-2 for impact testing, the request must be made at the time of order placement | POA |
| Other impact testing | POA |

7.5 Test certificates

| | £/tonne |
|--|---------|
| Test certificates supplied in accordance with EN 10204 Type 31 | Basis |
| Test certificates supplied to other EN 10204 Types | POA |
| Product analysis | POA |

7.6 Inspection test plan

| | £/tonne |
|--|---------|
| Where the customer requires sections manufacture to be in accordance with an agreed quality plan involving multiple inter-stage inspections, document reviews or other procedures, inspection charges will reflect the degree of inspection required by the quality plan and the number of inspection authorities involved | POA |



8. Additions

8.1 Cancellations

Any cancellation will be subject to additional charges. Cancellations post-rolling will not be accepted.

8.2 Carriage rates

Carriage rates will be applied accordingly. Please contact British Steel for details.

8.3 Storage costs

If due to late call-off by the customer, material remains in stock for more than two weeks following date made available, a storage fee of £1.50/t per week will be applied.

8.4 Certificate of approval

British Steel sections are fully compliant with the requirements of the Construction Products Directive (CPD 89/106/EEC).

Our Declaration of Conformity and Notified Body Approval certificates can be viewed online at:

www.britishsteel.co.uk/who-we-are/approvals-certifications

BRITISHSTEEL.CO.UK/CONSTRUCTION

A | PO Box 1, Brigg Road, Scunthorpe, North Lincolnshire, DN16 1BP
T | +44 (0)1724 404040 E | construction@britishsteel.co.uk

SASPL:ENG:112020

BUILDING STRONGER FUTURES

Care has been taken to ensure that the contents of this publication are accurate, but British Steel Limited and its subsidiaries and associated undertakings (having the meaning set out in the Companies Act 2006) do not accept responsibility or liability for errors or information that is found to be misleading.

Copyright British Steel 2020

British Steel Limited is registered in England under number 12303256 with registered office at Administration Building, Brigg Road, Scunthorpe, DN16 1XA.

