

Declaration of Performance (according to regulation EU No 305/2011)

Unique identification code of the product-type:
No. BS Section S235J0

Section S235J0 / 1.0114 according EN 10025-2

Intended use:

To be used in Metal Structures and Composite Metal and Concrete Structures

Manufacturer:

British Steel Limited PO Box 1, Brigg Road Scunthorpe, DN16 1BP

Tel: +44 (0)1724 404040

Website: www.britishsteel.co.uk

System of assessment and verification of constancy of performance of the product:

System 2+

Factory Production Control Notified Body No. 2814 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control.

The performance of the product identified in the Declared Performance is in conformity with the set of declared performance/s.

This declaration of performance is issued, in accordance with:

Regulation EU No 305/2011 under the sole responsibility of the manufacturer identified above.

Certificate No. 2814/CPR/LRQ0860859/1

Signed for and on behalf of the manufacturer by:

Richard Holcroft COO, British Steel Limited 1st July, 2021 Date

Essential characteristic	Declared Performance				Harmonise Standard	
Tolerances on	I&HS			0034		
dimensions		ange Tee	EN 10055			
and shape	Equal Angle		EN 10056-2			
	Unequal Angle		EN10056-2			
	Tapered Flange I		EN 10024			
	Bulb Flats		EN 10067			
	Channels		EN 10279			
Yield strength	Nominal thickness		Values			
(transverse)	(mm)		Min (MPa)			
	>	<=			4	
	_	16	23			
	16	40		225		
	40	63	215			
	63	80	2	15	_	
	80	100	2			
	100	150	19	195		
Tensile	Nominal	hickness	Values		1	
strength	(mm)		(MPa)		1	
(transverse)	> \	<=	min	max	1	
	-	-			EN10025-1	
	3	100	360	510	2004	
	100	150	350	500	2004	
	100	100	000			
			1		1	
F			1	1	1	
Florestics	Naminal	histores	Val		+	
Elongation (transverse)	Nominal thickness		Values min (%, 5.65√so)			
	(mm)		ININ (%, 5.65VSO)		4	
	>	<=			4	
	3	40	24		4	
	40	63	23		4	
	63	100	22		4	
	100	150	22		4	
Impact	10		071 1 0 0		I	
strength	J0		27J at	t - 0oC	1	
(longitudinal)	N. C. Lucc				4	
Weldability	Nominal thickness		Values		1	
CEV	(mm)		max (%)		4	
	>	<=			1	
	-	40	0.35		1	
	40	150	0.38			
Ī					1	
Durability	Nominal	thickness	Values	Values	7	
	(m		min (%)	max (%)	1	
	- (***	150	/	Mn: 1.40	1	
				Cu: 0.55	1	
				C: 0.17	I	
				P: 0.030	1	
				S: 0.030	1	
				N: 0.012	1	
					1	
					1	
					1	
					1	
				I	I	
				I	I	
				I	I	
				I	I	
				I	I	
				I	I	
				1	1	



Manufacturer:

2814

British Steel Limited PO Box 1, Brigg Road Scunthorpe, UK

20

Unique identification code of the product-type:

BS Section S235J0

Harmonised Standard : FN 10025-1 - 2004

Section S235J0 / 1.0114

Intended use:

To be used in Metal Structures and Composite Metal and Concrete Structures

Elongation:

Tensile Strength:

Yield Strength: EN 10025-2

Impact Strength: Weldability:
Durability:

Dangerous Substances: No Performance Determined

EU Notified Body

Lloyd's Register Verification B.V. K.P. van der Mandelelaan 41A Rotterdam, Netherlands Tel: +31 (0)10 4145088

Email : rotterdam@lr.org Website : www.lr.org