



**Declaration of Performance**  
(according to regulation EU No 305/2011)

Unique identification code of the product-type:  
No. BS Section S275ML

**Section S275ML / 1.8819 according EN 10025-4**

Intended use:  
To be used in Metal Structures and Composite Metal and  
Concrete Structures

Manufacturer:  
**British Steel Limited**  
PO Box 1, Brigg Road  
Scunthorpe, DN16 1BP

Tel: +44 (0)1724 404040

Website : [www.britishsteel.co.uk](http://www.britishsteel.co.uk)

System of assessment and verification of constancy of  
performance of the product:  
**System 2+**

Factory Production Control Notified Body No. 2814 performed the initial  
inspection of the manufacturing plant and of factory production control and the  
continuous surveillance, assessment, and evaluation of factory production  
control and issued the certificate of conformity of the factory production control.

The performance of the product identified in the Declared Performance is in  
conformity with the set of declared performance/s.

This declaration of performance is issued, in accordance with:  
Regulation EU No 305/2011 under the sole responsibility of the  
manufacturer identified above.

**Certificate No. 2814/CPR/LRQ0860859/1**

Signed for and on behalf of the manufacturer by:

Richard Holcroft  
COO, British Steel Limited

**1<sup>st</sup> July, 2021**  
Date

Essential characteristic	Declared Performance			Harmonised Standard	
Tolerances on dimensions and shape	I & H Sections		EN 10034	EN10025-1 2004	
	Equal Flange Tee		EN 10055		
Yield strength (transverse)	Equal Angle		EN 10056-2		
	Unequal Angle		EN10056-2		
	Tapered Flange I		EN 10024		
	Bulb Flats		EN 10067		
	Channels		EN 10279		
	Nominal thickness (mm)		Values Min (MPa)		
	>	<=			
	-	16	275		
16	40	265			
40	63	255			
63	80	245			
80	100	245			
100	120	240			
Tensile strength (transverse)	Nominal thickness (mm)		Values (MPa)		
	>	<=	min	max	
	5	40	370	530	
	40	63	360	520	
	63	120	350	510	
Elongation (transverse)	Nominal thickness (mm)		Values min (% 5.65√so)		
	>	<=			
	5	120	24		
Impact strength (longitudinal)			27J at - 50°C		
Weldability CEV	Nominal thickness (mm)		Values max (%)		
	>	<=			
	-	16	0.34		
	16	40	0.34		
	40	63	0.35		
	63	120	0.38		
Durability	Nominal thickness (mm)		Values min (%)	Values max (%)	
	-	120		Mn: 1.50 Cr: 0.30 Cu: 0.55 C: 0.13 Si: 0.50 P: 0.025 S: 0.020 Nb: 0.050 V: 0.08 Ti: 0.05 Ni: 0.30 Mo: 0.10 N: 0.015	



**2814**

Manufacturer:  
**British Steel Limited**  
PO Box 1, Brigg Road  
Scunthorpe, UK

20

Unique identification code of the product-type:  
**BS Section S275ML**

Harmonised Standard :  
EN 10025-1 – 2004

**Section S275ML / 1.8819**

Intended use:  
To be used in Metal Structures and Composite Metal  
and Concrete Structures

Elongation :  
Tensile Strength :  
Yield Strength : EN 10025-4  
Impact Strength :  
Weldability :  
Durability :

Dangerous Substances : No Performance Determined

EU Notified Body  
**Lloyd's Register Verification B.V.**  
K.P. van der Mandelelaan 41A  
Rotterdam, Netherlands  
Tel : +31 (0)10 4145088  
Email : [rotterdam@lr.org](mailto:rotterdam@lr.org)  
Website : [www.lr.org](http://www.lr.org)