



Declaration of Performance
The Construction Products (Amendment etc.) (EU Exit)
Regulations 2020 No 1359

Unique identification code of the product-type:
 No. BS Section S450J0

Section S450J0 / 1.0590 according EN10025-2

Intended use:
 To be used in Metal Structures and Composite Metal and
 Concrete Structures

Manufacturer:
British Steel Limited
PO Box 1, Brigg Road
Scunthorpe, DN16 1BP

Tel: +44 (0)1724 404040

Website : www.britishsteel.co.uk

System of assessment and verification of constancy of
 performance of the product:
System 2+

Factory Production Control Assessment body No. 0038 performed the initial
 inspection of the manufacturing plant and of factory production control and the
 continuous surveillance, assessment, and evaluation of factory production
 control and issued the certificate of conformity of the factory production control.

The performance of the product identified in the Declared Performance is in
 conformity with the set of declared performance/s.
 This declaration of performance is issued, in accordance with: Regulation (EU
 Exit) Regulations 2020 No 1359, under the sole responsibility of the
 manufacturer identified above.

Certificate No. 0038/CPR/LRQ0860859/1

Signed for and on behalf of the manufacturer by:

Richard Holcroft
 COO, British Steel Limited

1st July, 2021
 Date

| Essential characteristic | Declared Performance | | | | Harmonised Standard |
|------------------------------------|------------------------|-----|-------------------------------------|--|---------------------|
| | Nominal thickness (mm) | | Values (MPa) | | |
| Tolerances on dimensions and shape | I & H Sections | | EN 10034 | | EN10025-1 2004 |
| | Equal Flange Tee | | EN 10055 | | |
| | Equal Angle | | EN 10056-2 | | |
| | Unequal Angle | | EN10056-2 | | |
| | Tapered Flange I | | EN 10024 | | |
| | Bulb Flats | | EN 10067 | | |
| | Channels | | EN 10279 | | |
| Yield strength (transverse) | Nominal thickness (mm) | | Values Min (MPa) | | EN10025-1 2004 |
| | > | <= | | | |
| | - | 16 | 450 | | |
| | 16 | 40 | 430 | | |
| | 40 | 63 | 410 | | |
| | 63 | 80 | 390 | | |
| | 80 | 100 | 380 | | |
| Tensile strength (transverse) | Nominal thickness (mm) | | Values (MPa) | | EN10025-1 2004 |
| | > | <= | min | max | |
| | 3 | 100 | 550 | 720 | |
| | 100 | 150 | 530 | 700 | |
| | | | | | |
| | | | | | |
| | | | | | |
| Elongation (transverse) | Nominal thickness (mm) | | Values min (% 5.65√s ₀) | | EN10025-1 2004 |
| | > | <= | | | |
| | 3 | 150 | 17 | | |
| | | | | | |
| Impact strength (longitudinal) | | | 27J at - 0oC | | EN10025-1 2004 |
| | | | | | |
| Weldability CEV | Nominal thickness (mm) | | Values max (%) | | EN10025-1 2004 |
| | > | <= | | | |
| | - | 30 | 0.47 | | |
| | 30 | 40 | 0.49 | | |
| | 40 | 150 | 0.49 | | |
| Durability | Nominal thickness (mm) | | Values min (%) | Values max (%) | EN10025-1 2004 |
| | - | 40 | | Mn: 1.70 Cu: 0.55 C: 0.20 (>30mm 0.22) Si: 0.55 P: 0.03 S: 0.03 N: 0.025 | |
| | 40 | 150 | | Mn: 1.70 Cu: 0.55 C: 0.22 Si: 0.55 P: 0.03 S: 0.03 N: 0.025 | |
| | | | | | |



0038

Manufacturer:
British Steel Limited
PO Box 1, Brigg Road
Scunthorpe, UK

20

Unique identification code of the product-type:
BS Section S450J0

Harmonised Standard :
 EN 10025-1 – 2004

Section S450J0 / 1.0590

Intended use:
 To be used in Metal Structures and Composite Metal
 and Concrete Structures

Elongation :
 Tensile Strength :
 Yield Strength : EN10025-2
 Impact Strength :
 Weldability :
 Durability :

Dangerous Substances : No Performance Determined

UK Conformity Assessment Body
Lloyds Register Verification Ltd
71 Fenchurch Street, London, EC3M 4BS
Tel :+44 (0)207 423 2428
Email : ecdirectives@lr.org
Website : www.lr.org