



Declaration of Performance
The Construction Products (Amendment etc.) (EU Exit)
Regulations 2020 No 1359

Unique identification code of the product-type:
 No. BS Section S235J0

Section S235J0 / 1.0114 according EN 10025-2

Intended use:
 To be used in Metal Structures and Composite Metal and
 Concrete Structures

Manufacturer:
British Steel Limited
PO Box 1, Brigg Road
Scunthorpe, DN16 1BP

Tel: +44 (0)1724 404040

Website : www.britishsteel.co.uk

System of assessment and verification of constancy of
 performance of the product:
System 2+

Factory Production Control Assessment body No. 0038 performed the initial
 inspection of the manufacturing plant and of factory production control and the
 continuous surveillance, assessment, and evaluation of factory production
 control and issued the certificate of conformity of the factory production control.

The performance of the product identified in the Declared Performance is in
 conformity with the set of declared performance/s.
 This declaration of performance is issued, in accordance with: Regulation (EU
 Exit) Regulations 2020 No 1359, under the sole responsibility of the
 manufacturer identified above.

Certificate No. 0038/CPR/LRQ0860859/1

Signed for and on behalf of the manufacturer by:

Richard Holcroft
 COO, British Steel Limited

1st July, 2021
 Date

Essential characteristic	Declared Performance				Harmonised Standard
	Nominal thickness (mm)		Values (MPa)		
Tolerances on dimensions and shape	I & H Sections		EN 10034		EN10025-1 2004
	Equal Flange Tee		EN 10055		
	Equal Angle		EN 10056-2		
	Unequal Angle		EN10056-2		
	Tapered Flange I		EN 10024		
	Bulb Flats		EN 10067		
	Channels		EN 10279		
Yield strength (transverse)	Nominal thickness (mm)		Values (MPa)		EN10025-1 2004
	>	<=	Min		
	-	16	235		
	16	40	225		
	40	63	215		
	63	80	215		
	80	100	215		
Tensile strength (transverse)	Nominal thickness (mm)		Values (MPa)		EN10025-1 2004
	>	<=	min	max	
	3	100	360	510	
	100	150	350	500	
Elongation (transverse)	Nominal thickness (mm)		Values min (% 5.65√s ₀)		EN10025-1 2004
	>	<=			
	3	40	24		
	40	63	23		
	63	100	22		
Impact strength (longitudinal)	Nominal thickness (mm)		Values		EN10025-1 2004
	J0		27J at - 0oC		
Weldability CEV	Nominal thickness (mm)		Values max (%)		EN10025-1 2004
	>	<=			
	-	40	0.35		
	40	150	0.38		
Durability	Nominal thickness (mm)		Values min (%)	Values max (%)	EN10025-1 2004
	-	150		Mn: 1.40 Cu: 0.55 C: 0.17 P: 0.030 S: 0.030 N: 0.012	



0038

Manufacturer:
British Steel Limited
PO Box 1, Brigg Road
Scunthorpe, UK

20

Unique identification code of the product-type:
BS Section S235J0

Harmonised Standard :
 EN 10025-1 – 2004

Section S235J0 / 1.0114

Intended use:
 To be used in Metal Structures and Composite Metal
 and Concrete Structures

Elongation :
 Tensile Strength :
 Yield Strength : EN 10025-2
 Impact Strength :
 Weldability :
 Durability :

Dangerous Substances : No Performance Determined

UK Conformity Assessment Body
Lloyds Register Verification Ltd
71 Fenchurch Street, London, EC3M 4BS
Tel :+44 (0)207 423 2428
Email : ecdirectives@lr.org
Website : www.lr.org