



**Declaration of Performance**  
**The Construction Products (Amendment etc.) (EU Exit)**  
**Regulations 2020 No 1359**

Unique identification code of the product-type:  
 No. BS Section S355M

**Section S355M / 1.8823 according EN 10025-4**

Intended use:  
 To be used in Metal Structures and Composite Metal and  
 Concrete Structures

Manufacturer:  
**British Steel Limited**  
**PO Box 1, Brigg Road**  
**Scunthorpe, DN16 1BP**

**Tel: +44 (0)1724 404040**

**Website : www.britishsteel.co.uk**

System of assessment and verification of constancy of  
 performance of the product:  
**System 2+**

Factory Production Control Assessment body No. 0038 performed the initial  
 inspection of the manufacturing plant and of factory production control and the  
 continuous surveillance, assessment, and evaluation of factory production  
 control and issued the certificate of conformity of the factory production control.

The performance of the product identified in the Declared Performance is in  
 conformity with the set of declared performance/s.  
 This declaration of performance is issued, in accordance with: Regulation (EU  
 Exit) Regulations 2020 No 1359, under the sole responsibility of the  
 manufacturer identified above.

**Certificate No. 0038/CPR/LRQ0860859/1**

Signed for and on behalf of the manufacturer by:

Richard Holcroft  
 COO, British Steel Limited

**1<sup>st</sup> July, 2021**  
 Date

Essential characteristic	Declared Performance			Harmonised Standard	
Tolerances on dimensions and shape	I & H Sections Equal Flange Tee Equal Angle Unequal Angle Tapered Flange I Bulb Flats Channels	EN 10034 EN 10055 EN 10056-2 EN10056-2 EN 10024 EN 10067 EN 10279		EN10025-1 2004	
Yield strength (transverse)	Nominal thickness (mm)	Values Min (MPa)			
	>	<=			
	-	16	355		
	16	40	345		
	40	63	335		
	63	80	325		
	80	100	325		
100	150	320			
Tensile strength (transverse)	Nominal thickness (mm)	Values (MPa)			
	>	<=	min		max
	0	40	470		630
	40	63	450		610
	63	80	440		600
	80	100	440	600	
	100	150	430	590	
Elongation (transverse)	Nominal thickness (mm)	Values min (% 5.65√so)			
	>	<=			
	0	150	22		
Impact strength (longitudinal)		40J at - 20oC			
Weldability CEV	Nominal thickness (mm)	Values max (%)			
	>	<=			
	-	16	0.39		
	16	40	0.39		
	40	63	0.40		
	63	120	0.45		
	63	120	0.45		
Durability	Nominal thickness (mm)	Values min (%)	Values max (%)		
	-	120	Mn: 1.60 Cr: 0.30 Cu: 0.55 C: 0.14 Si: 0.50 P: 0.030 S: 0.025 Nb: 0.050 V: 0.10 Ti: 0.05 Ni: 0.50 Mo: 0.10 N: 0.015		



**0038**

Manufacturer:  
**British Steel Limited**  
**PO Box 1, Brigg Road**  
**Scunthorpe, UK**

20

Unique identification code of the product-type:  
**BS Section S355M**

Harmonised Standard :  
 EN 10025-1 – 2004

**Section S355M / 1.8823**

Intended use:  
 To be used in Metal Structures and Composite Metal  
 and Concrete Structures

Elongation :  
 Tensile Strength :  
 Yield Strength : EN 10025-4  
 Impact Strength :  
 Weldability :  
 Durability :

Dangerous Substances : No Performance Determined

UK Conformity Assessment Body  
**Lloyds Register Verification Ltd**  
**71 Fenchurch Street, London, EC3M 4BS**  
**Tel :+44 (0)207 423 2428**  
**Email : ecdirectives@lr.org**  
**Website : www.lr.org**