



Declaration of Performance
The Construction Products (Amendment etc.) (EU Exit)
Regulations 2020 No 1359

Unique identification code of the product-type:
 No. BS Section S355ML

Section S355ML / 1.8834 according EN 10025-4

Intended use:
 To be used in Metal Structures and Composite Metal and
 Concrete Structures

Manufacturer:
British Steel Limited
PO Box 1, Brigg Road
Scunthorpe, DN16 1BP

Tel: +44 (0)1724 404040

Website : www.britishsteel.co.uk

System of assessment and verification of constancy of
 performance of the product:
System 2+

Factory Production Control Assessment body No. 0038 performed the initial
 inspection of the manufacturing plant and of factory production control and the
 continuous surveillance, assessment, and evaluation of factory production
 control and issued the certificate of conformity of the factory production control.

The performance of the product identified in the Declared Performance is in
 conformity with the set of declared performance/s.
 This declaration of performance is issued, in accordance with: Regulation (EU
 Exit) Regulations 2020 No 1359, under the sole responsibility of the
 manufacturer identified above.

Certificate No. 0038/CPR/LRQ0860859/1

Signed for and on behalf of the manufacturer by:

Richard Holcroft
 COO, British Steel Limited

1st July, 2021
 Date

Essential characteristic	Declared Performance			Harmonised Standard
Tolerances on dimensions and shape	I & H Sections		EN 10034	EN10025-1 2004
	Equal Flange Tee		EN 10055	
Equal Angle		EN 10056-2		
Unequal Angle		EN10056-2		
Tapered Flange I		EN 10024		
Bulb Flats		EN 10067		
Channels		EN 10279		
Yield strength (transverse)	Nominal thickness (mm)		Values Min (MPa)	
	>	<=		
	-	16	355	
	16	40	345	
	40	63	335	
	63	80	325	
	80	100	325	
Tensile strength (transverse)	Nominal thickness (mm)		Values (MPa)	
	>	<=	min max	
	0	40	470 630	
	40	63	450 610	
	63	80	440 600	
	80	100	440 600	
	100	150	430 590	
Elongation (transverse)	Nominal thickness (mm)		Values min (% 5.65√s ₀)	
	>	<=		
	0	150	22	
Impact strength (longitudinal)	27J at - 50°C			
Weldability CEV	Nominal thickness (mm)		Values max (%)	
	>	<=		
	-	16	0.39	
	16	40	0.39	
	40	63	0.40	
	63	120	0.45	
Durability	Nominal thickness (mm)		Values min (%) Values max (%)	
	-	120	Mn: 1.60 Cr: 0.30 Cu: 0.55 C: 0.14 Si: 0.50 P: 0.025 S: 0.020 Nb: 0.050 V: 0.10 Ni: 0.50 Mo: 0.10 N: 0.015	



0038

Manufacturer:
British Steel Limited
PO Box 1, Brigg Road
Scunthorpe, UK

20

Unique identification code of the product-type:
BS Section S355ML

Harmonised Standard :
 EN 10025-1 – 2004

Section S355ML / 1.8834

Intended use:
 To be used in Metal Structures and Composite Metal
 and Concrete Structures

Elongation :
 Tensile Strength :
 Yield Strength : EN 10025-4
 Impact Strength :
 Weldability :
 Durability :

Dangerous Substances : No Performance Determined

UK Conformity Assessment Body
Lloyds Register Verification Ltd
71 Fenchurch Street, London, EC3M 4BS
Tel :+44 (0)207 423 2428
Email : ecdirectives@lr.org
Website : www.lr.org