



Declaration of Performance
(according to regulation EU No 305/2011)

Unique identification code of the product-type:
No. BS Section S355J0

Section S355J0 / 1.0553 according EN 10025-2

Intended use:
To be used in Metal Structures and Composite Metal and Concrete Structures

Manufacturer:
British Steel Limited
Brigg Road
Scunthorpe, DN16 1XA

Tel: +44 (0)1724 404040

Website : www.britishsteel.co.uk

System of assessment and verification of constancy of performance of the product:
System 2+

Factory Production Control Notified Body No. 2814 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control.

The performance of the product identified in the Declared Performance is in conformity with the set of declared performance/s.

This declaration of performance is issued, in accordance with: Regulation EU No 305/2011 under the sole responsibility of the manufacturer identified above.

Certificate No. 2814/CPPR/LRQ0860859/1

Signed for and on behalf of the manufacturer by:

Chris Vaughan
SHEQ Director,
British Steel Limited

1st February, 2023
Date

Essential characteristic	Declared Performance			Harmonised Standard	
Tolerances on dimensions and shape	I & H Sections		EN 10034	EN10025-1 2004	
	Equal Flange Tee		EN 10055		
Yield strength (transverse)	Equal Angle		EN 10056-2		
	Unequal Angle		EN10056-2		
	Tapered Flange I		EN 10024		
	Bulb Flats		EN 10067		
	Channels		EN 10279		
	Nominal thickness (mm)		Values Min (MPa)		
	>	<=			
	-	16	355		
16	40	345			
40	63	335			
63	80	325			
80	100	315			
100	150	295			
Tensile strength (transverse)	Nominal thickness (mm)		Values (MPa)		
	>	<=	min	max	
	3	100	470	630	
	100	150	450	600	
Elongation (transverse)	Nominal thickness (mm)		Values min (% 5.65√s ₀)		
	>	<=			
	3	40	22		
	40	63	21		
	63	100	20		
100	150	18			
Impact strength (longitudinal)	J0		27J at - 0oC		
Weldability CEV	Nominal thickness (mm)		Values max (%)		
	>	<=			
	-	30	0.45		
	30	40	0.47		
	40	150	0.47		
Durability	Nominal thickness (mm)		Values min (%)	Values max (%)	
	-	40		Mn: 1.60 Cu: 0.55 C: 0.20 (>30mm 0.22) Si: 0.55 P: 0.030 S: 0.030 N: 0.012	
	40	150		Mn: 1.60 Cu: 0.55 C: 0.22 Si: 0.55 P: 0.030 S: 0.030 N: 0.012	



2814

Manufacturer:
British Steel Limited
Brigg Road
Scunthorpe, UK

20

Unique identification code of the product-type:
BS Section S355J0

Harmonised Standard :
EN 10025-1 – 2004

Section S355J0 / 1.0553

Intended use:
To be used in Metal Structures and Composite Metal and Concrete Structures

Elongation :
Tensile Strength :
Yield Strength : EN 10025-2
Impact Strength :
Weldability :
Durability :

Dangerous Substances : No Performance Determined

EU Notified Body
LRQA Verification B.V,
George Hintzenweg 77, 3068 AX
Rotterdam, Netherlands
Tel : +31 (0)10 4145088
Email : marc.verboon@lrqa.com
Website : www.lrqa.com